


HS United European Connectors

Ringkabelschuh	Artikel-Nr.	Leiter- quer- schnitt	Material	Ober- fläche	L1	D1	D2	Mate- rial- stärke	Verp.- Ein- heit
		mm ²			mm	mm	mm	mm	
 <p>Längstransport * DIN 46 225</p>	23.211.110	0,5 – 1,0	CuZn	blank	17,5	9,5	3,2	0,6	6.000
	23.211.120		CuZn	Sn					
	23.211.310		CuSn	blank					
	23.211.320		CuSn	Sn					
	23.811.110	0,5 – 1,0	CuZn	blank	17,5	9,5	3,8	0,6	6.000
	23.811.120		CuZn	Sn					
	23.811.310		CuSn	blank					
	23.811.320		CuSn	Sn					
	24.311.110	0,5 – 1,0	CuZn	blank	17,5	9,5	4,3	0,6	6.000
	24.311.120		CuZn	Sn					
	24.311.310		CuSn	blank					
	24.311.320		CuSn	Sn					
	25.311.110	0,5 – 1,0	CuZn	blank	17,5	9,5	5,3*	0,6	6.000
	25.311.120		CuZn	Sn					
	25.311.310		CuSn	blank					
	25.311.320		CuSn	Sn					
26.511.110	0,5 – 1,0	CuZn	blank	17,5	9,5	6,5	0,6	6.000	
26.511.120		CuZn	Sn						
26.511.310		CuSn	blank						
26.511.320		CuSn	Sn						